


## MAXIMO® XXL





## **TECHNICAL DATA** MAXIMO® XXL

In vehicles with a low resonant frequency, seats with a low-frequency suspension maximize comfort by absorbing vertical vibrations and jolts. This prevents bouncing as a result of resonance build-up. The lower the suspension's resonant frequency, the greater the comfort experienced by the driver.



Pneumatic Suspension

Automatic

Positioning

System



Frequency

Suspension

**Automatic** 

Weight

Adjustment

Pneumatic Lumbar



Support





Fore/Aft Isolator

Passive Climate System

Features • Standard O Optional

	MAXIMO® XXL
Article no. fabric	1292187
APS (Automatic positioning system)	•
1 Shock absorber adjustable	
Suspension	
Pneumatic suspension with compressor 12V	•
Cow-frequency suspension	•
Suspension stroke 100 mm	•
Weight adjustment 50 - 130 kg, automatic	•
2 Height adjustment 80 mm infinite (air-assisted)	
Climate system passive	•
3 Fore/aft adjustment 210 mm	•
4 Fore/aft isolator	•
5 Lumbar support pneumatic	•

	MAXIMO® XXL
6 Adjustable backrest angle	•
7 Backrest extension	•
8 Restraint system	•
Seat cushion width	530 mm
Adjustable seat cushion depth and angle	•
Operator presence switch (OPS)	•
OPTIONAL FEATURES	
Document box	0
Armrests foldable	
65 x 270 mm, height adjustable	0
80 x 320 mm, height adjustable, foldable	0
80 x 380 mm, height adjustable, foldable	0
Seat heating	0

## Measurements (installation dimensions)

